

# Colored Cable Ties



  
**LISTED**  
 POSITIONING DEVICE  
 33AS  
 UL STANDARD UL62275  
 FILE NO: E530766  
 TYPE: 21S

- **Material: Nylon 6/6**
- **UL Listed, File No. E530766 Positioning Device 33AS**
- **UL Standard UL 62275 TYPE 21 or 21S**
- **Operating temperature range -40° to +185° F**



**Kable Kontrol® Nylon Colored Zip Ties** are an ideal and cost-effective option for all applications that require easy identification. The choice between twelve different colors will help you to easily spot the difference between whatever you are securing. Colored nylon zip ties can be used outdoors. However, they will only serve as a temporary solution since they are not UV protected.

| SKU        | Length | Width | Strength (lbs) | Color                             | Pack Quantity |
|------------|--------|-------|----------------|-----------------------------------|---------------|
| CT204CL    | 4"     | 2.5mm | 18 lbs.        | Rd  Or  Y  Bl  Gn  Br  Pr  Gy     | 100           |
| CT261CL+   | 8"     | 4.8mm | 50 lbs.        | Rd  Or  Y  Bl  Gn  Br  Pr  Pk  Gy | 100           |
| CT262CL+   | 11"    | 4.8mm | 50 lbs.        | Rd  Or  Y  Bl  Gn  Br  Pr  Gy     | 100           |
| CT265CL+   | 14"    | 4.8mm | 50 lbs.        | Rd  Or  Y  Bl  Gn  Br  Pr  Gy     | 100           |
| CT-14-120+ | 14"    | 7.6mm | 120 lbs.       | Rd  Or  Y  Bl  Gn  Br  Pr  Gy     | 100           |
| CT504FL    | 4"     | 2.5mm | 18 lbs.        | Or  Bl  Pk  Yw<br>FLUORESCENT     | 100           |
| CT508FL+   | 8"     | 4.8mm | 50 lbs.        | Or  Bl  Pk  Yw<br>FLUORESCENT     | 100           |
| CT511FL+   | 11"    | 4.8mm | 50 lbs.        | Or  Bl  Pk  Yw<br>FLUORESCENT     | 100           |
| CT514FL+   | 14"    | 4.8mm | 50 lbs.        | Or  Bl  Pk  Yw<br>FLUORESCENT     | 100           |